

ACCESSORIES



24V

48V

400V

Side guide



Side guides are used for reliably guiding the product on roller conveyors and belt conveyors, as well as on the corresponding components. We offer the side guides in an aluminum and a polymer version. In particular, because of the flexible material, the guides can be adjusted to the material flow in curves, as well as when merging and diverting.

| Designation | Dimensions | Reference number |
|---------------------|-------------------|------------------|
| Aluminum side guide | 40 x 15 x 2000 mm | 63133351 |
| Polymer side guide | 40 x 15 x 2000 mm | 63010049 |

Side guide holder



The side guide profile is attached to the universal support with the side guide holder.

| Designation | Dimensions | Reference number |
|-------------------|-----------------|------------------|
| Side guide holder | 46 x 28 x 22 mm | 63010248 |

Side guide connector



Side guides are connected to each other at the transition of two modules with the side guide connector.

| Designation | Dimensions | Reference number |
|----------------------|------------|------------------|
| Side guide connector | 70 x 28 mm | 63010050 |

End cap for side guide profile



An end cap is attached to the end of a side guide. The contour prevents products from being caught.

| Designation | Dimensions | Reference number |
|--------------------------------|------------------|------------------|
| End cap for side guide profile | 100 x 40 x 40 mm | 63010039 |