



Product overview

About Interroll

Established in 1959, Interroll has grown to become the world's leading supplier of key products for internal logistics. Whether boxes, pallets or soft goods are to be handled, no other supplier has such a complete product range on offer. That is why system integrators, OEMs and operators select Interroll as their partner for their internal logistics business. Worldwide. The Interroll global network ensures quick delivery and superior service for every local customer. We inspire our customers and provide opportunities for them to increase efficiency.

interroll.com

INSPIRED BY EFFICIENCY

EN | March | 2017 | 200 | T@W

©2017 INTERROLL



Interroll Supermarket Solutions
Smooth stop-and-go in the checkout zone

INSPIRED BY EFFICIENCY

Interroll Supermarket Solutions

You can find our products in supermarkets' checkout and cashier systems worldwide, perfectly tailored to the specific requirements of checkout systems. Engineers especially prefer the fast and easy design and installation of Interroll products, which make construction and mounting a simple task.



We are close to our customers, even where they least expect it: Six times out of 10, the checkout stands where these items run, are powered by Interroll. Proven.



The new **Softstart Control** motor controller in a **compact design** perfectly covers the requirements of checkout manufacturers and reduces the complexity of installation. The integrated start capacitor allows **easy start-up** of the one-phase drive. With only one Softstart Control it is possible to control the inlet and/or outlet belt and connect all necessary accessories like light

barrier, foot-pedal and signal light. Moreover, a **smooth start and stop** of checkout belt is possible, even with a heavy load, thanks to the integrated motor soft starter. This very useful function helps prevent tilting goods and **reduce unnecessary cleaning, downtime** of the checkout, and loss of goods.

Compact drive

- Space-saving drum motor
- Plug-and-play installation
- Cost-effective operation

Plug-and-Play Cassette

- Quick and easy to install
- Pretested and "run-in"
- Easy belt change with quick tension/release system

Softstart Control

- Smooth start and stop
- Easy installation
- One control for all
- Built-in safety

Accessories

A wide range of accessories like light barrier, signal lights and foot-pedal complete the offering, including proximity switch to avoid injury of employees or customers.

Technical data	
Power supply	220-240 V / 50 Hz
Max. rated power consumption controller	700 VA
Max. rated power consumption each drum motor (230V / 50 Hz)	200 VA
Max. rated power consumption each light output (220-240V / 50 Hz)	100 VA
Main fuse	4 A
Motor capacitor	6 uF / 450 V
Operating temperature	+5 °C - +40 °C
Operating relative humidity	10 % - 80 %
Dimensions	178x55x223 mm
Mass	680 g